

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Double Al-foil shielding

Product information:

CLV114 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. It has a aluminium foil shielding with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected.



Components:

- CableType: SVGA214 - Video Cable

Properties:



Product Features:

Application	AV & IT
Series	Classic Series

Physical Characteristics:

Inner conductor	Insulation	Material	FPE 1.55 mm (Ø)
		Colours	White
	Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap
		Drain wire	BC 7 x 0.12 mm (Ø) (OFC)
	Insulation	Material	PVC 0.9 mm (Ø)
			PVC 1 mm (Ø)
		Colours	Black
		Material	PVC 0.9 mm (Ø)
		Colours	Green / Blue ; Orange / Yellow ; Brown / Red
Overall shielding	Aluminium foil		Al-mylar, 100% coverage - 25% Overlap
	Drain wire		BC 7 x 0.16 mm (Ø) (OFC)
Outer jacket	Material		PVC 7.5 mm (Ø)
	Colours		Black
Type of cable			75 Ω VGA video cable
Inner conductor	Material		BC 7 x 0.12 mm (Ø) (OFC)
			BC 10 x 0.12 mm (Ø) (OFC)
			BC 10 x 0.12 mm (Ø) (OFC)
Filling			Cotton Yarn
Inner conductor	American Wire Gauge		28 AWG

Variants:

- CLV114/1.5 - 1,5 meter
- CLV114/15 - 15 meter
- CLV114/25 - 25 meter
- CLV114/30 - 30 meter

Component details:

SVGA214

Video Cable

This cable is a cable only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the productsheet for detailed information.