

Highlights:


- Slim Ø 3.2 mm diameter
- PoE tested and approved (IEEE 802.3 af)
- LSHF jacket
- Tested up to 500 Mhz
- Thin, flexible and smooth cable jacket
- Time and space saving in rack applications
- Better airflow due to slim design
- Snagless & compact connector
- Multicoloured cables

**Product information:**

The CSD560 series is a series of Ultra-slim CAT6A U/UTP cables, which come available in a wide variety of lengths and colours. They offer reliable interconnections in various applications, ranging from general-purpose office computer systems to digital AV network systems. The ultra-slim construction with an outer diameter of only Ø 3.2 mm offers an elegant solution for office patch usage while guaranteeing the best possible space saving and airflow in rack applications. The compact and snagless connector design and numerous variants and colours offer reliable connections and a clear overview when wiring racks for various applications or protocols.



Properties:



Product Features:

Application	AV & IT
Series	Connect Series

Physical Characteristics:

Type of cable	U/UTP CAT6A Networking cable	
Outer jacket	Material	LSHF 3.2 mm (Ø)
Inner conductor	American Wire Gauge	30 AWG
Outer jacket	Colours	Black
		Green
		White
		Blue
		Red
		Yellow
		Grey
		Violet
		Orange
Connection type	RJ45 male to RJ45 male	

Variants:

- CSD560B/0.15 - Black version - 0.15 meter
- CSD560B/0.3 - Black version - 0.3 meter
- CSD560B/0.5 - Black version - 0.5 meter
- CSD560B/1 - Black version - 1 meter
- CSD560B/1.5 - Black version - 1.5 meter
- CSD560B/2 - Black version - 2 meter
- CSD560B/3 - Black version - 3 meter
- CSD560B/5 - Black version - 5 meter
- CSD560BU/0.15 - Blue version - 0.15 meter
- CSD560BU/0.3 - Blue version - 0.3 meter
- CSD560BU/0.5 - Blue version - 0.5 meter
- CSD560BU/1 - Blue version - 1 meter
- CSD560BU/1.5 - Blue version - 1.5 meter
- CSD560BU/2 - Blue version - 2 meter
- CSD560G/0.15 - Green version - 0.15 meter
- CSD560G/0.3 - Green version - 0.3 meter
- CSD560G/0.5 - Green version - 0.5 meter
- CSD560G/1 - Green version - 1 meter
- CSD560G/1.5 - Green version - 1.5 meter
- CSD560G/2 - Green version - 2 meter
- CSD560GY/0.15 - Grey version - 0.15 meter
- CSD560GY/0.3 - Grey version - 0.3 meter
- CSD560GY/0.5 - Grey version - 0.5 meter
- CSD560GY/1 - Grey version - 1 meter
- CSD560GY/1.5 - Grey version - 1.5 meter
- CSD560GY/2 - Grey version - 2 meter
- CSD560OR/0.15 - Orange version - 0.15 meter
- CSD560OR/0.3 - Orange version - 0.3 meter
- CSD560OR/0.5 - Orange version - 0.5 meter
- CSD560OR/1 - Orange version - 1 meter
- CSD560OR/1.5 - Orange version - 1.5 meter
- CSD560OR/2 - Orange version - 2 meter
- CSD560R/0.15 - Red version - 0.15 meter
- CSD560R/0.3 - Red version - 0.3 meter
- CSD560R/0.5 - Red version - 0.5 meter
- CSD560R/1 - Red version - 1 meter
- CSD560R/1.5 - Red version - 1.5 meter
- CSD560R/2 - Red version - 2 meter
- CSD560V/0.15 - Violet version - 0.15 meter
- CSD560V/0.3 - Violet version - 0.3 meter
- CSD560V/0.5 - Violet version - 0.5 meter
- CSD560V/1 - Violet version - 1 meter
- CSD560V/1.5 - Violet version - 1.5 meter
- CSD560V/2 - Violet version - 2 meter
- CSD560W/0.15 - White version - 0.15 meter
- CSD560W/0.3 - White version - 0.3 meter
- CSD560W/0.5 - White version - 0.5 meter
- CSD560W/1 - White version - 1 meter
- CSD560W/1.5 - White version - 1.5 meter
- CSD560W/2 - White version - 2 meter
- CSD560Y/0.15 - Yellow version - 0.15 meter
- CSD560Y/0.3 - Yellow version - 0.3 meter
- CSD560Y/0.5 - Yellow version - 0.5 meter
- CSD560Y/1 - Yellow version - 1 meter

- CSD560Y/1.5 - Yellow version - 1.5 meter
- CSD560Y/2 - Yellow version - 2 meter