


Highlights:

- Triple shielding

Product information:

The HDM24 is a bulk reel of quality 24AWG-size HDMI cable. Since this thicker cable offers less resistance, it is highly suitable for relatively longer distances. It is designed for installation using the PROCAB contractor series equipment. Lengths below 10m will perform as HIGH SPEED HDMI with ETHERNET. Lengths between 10 and 15m will perform at STANDARD SPEED HDMI with ETHERNET standards. Recommended HD distance : 20 m (1080p)




Certification:



Properties:



Inner Conductors:



Shielding:



Product Features:

| | |
|-------------|--------------------|
| Application | AV & IT |
| Series | Bulk & Accessories |

Physical Characteristics:

| | | | |
|-------------------|---------------------|----------------|---------------------------------------|
| Inner conductor | Insulation | Material | FM-PE 1.4 mm (Ø) (5 pair) |
| | | | HD-PE 0.9 mm (Ø) (1 pair) |
| | | | HD-PE 0.9 mm (Ø) (2 cond.) |
| | Shielding | Aluminium foil | Al-mylar, 100% coverage - 25% Overlap |
| | | Drain wire | BC 1 x 0.511 mm (Ø) (OFC) |
| Overall shielding | Aluminium foil | | Al-mylar, 100% coverage - 25% Overlap |
| | Drain wire | | BC 1 x 0.511 mm (Ø) (OFC) |
| | Braiding | | AL-MG 16 x 12 x 0.12 mm (Ø) |
| Outer jacket | Material | | PVC 9.5 mm (Ø) |
| | Colours | | Black |
| Inner conductor | Material | | BC 1 x 0.511 mm (Ø) (OFC) (5 pair) |
| | | | TC 7 x 0.16 mm (Ø) (OFC) (1 pair) |
| Type of cable | | | HDMI High Speed with Ethernet |
| Inner conductor | American Wire Gauge | | 24 AWG (5 pair) |
| | | | 26 AWG (1 pair) |
| | | | 26 AWG (2 cond.) |

Mechanical Characteristics:

| | | |
|-------------------|---------------------|------------------------|
| Temperature range | Fixed installation | - 104 °F till + 176 °F |
| | Mobile installation | - 59 °F till + 140 °F |
| Bending radius | Fixed installation | 6 x outer diameter |
| | Mobile installation | 8 x outer diameter |