

Highlights:

- 15 AWG thin and dense stranded conductors
- Flexible PVC jacket

Product information:

The LS series cables are high quality and flexible double isolated loudspeaker cables. They are suitable for use in indoor as well as outdoor applications. Each conductor is fitted with a highly flexible jacket made of PVC. Both conductors are twisted with two cords, which ensures the great strength and flexibility of the cable. The whole inner section is packed by a paper foil into a highly flexible outer jacket made of PVC. These cables have been designed for connection of loudspeakers in fixed or mobile sound systems.



Properties:



Inner Conductors:



Product Features:

Application

AV & IT

Rental & MI

Series

Bulk & Accessories

Physical Characteristics:

Type of cable	2-core loudspeaker cable		
Inner conductor	Material	BC 133 x 0.12 mm (Ø) (OFC)	
	Section	0.0023 ^{“2}	
	Insulation	Material	PVC 2.8 mm (Ø)
	Number of conductors	2	
Filling		Cotton Yarn	
Separator		Cotton paper	
Inner conductor	American Wire Gauge	15 AWG	
	Insulation	Colours	Red / Blue
Outer jacket	Material	Flexible PVC 8 mm (Ø)	
	Colours	Black	
		White	
Inner conductor	Conductor twisting	Yes	

Mechanical Characteristics:

Temperature range	Fixed installation	- 40 °C till + 80 °C
	Mobile installation	- 25 °C till + 70 °C
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Capacitance	Cond/Cond	95 pF / m @ 1 kHz
Lead resistance		1.2 Ω / 100 m
Cable Crosstalk		Min. 64 dB / 100 m

Cross sections:

