



# Loudspeaker cable - 5 x 0,4 mm<sup>2</sup> - 21 AWG - with steel tension

# Highlights:

- · Flexible PVC jacket
- 5 x 0.4 mm<sup>2</sup> (21 AWG) stranded conductors
- · Integrated 0.56 mm² steel core for loudspeaker suspending

#### Product information:

The LSS504 is a high-quality and double isolated loudspeaker cable, suitable for indoor as well as outdoor use. The cable core section consists of 5 individual isolated conductors with a highly flexible PVC jacked and a cable section of 0.4 mm². What makes the LSS504 special is the added steel core in the center of the cable. This makes the LSS504 the perfect solution for hanging loudspeakers in 100V installations. This way, an external safety cable is no longer needed and the speakers design stays untouched. The 5 cable cores, each of them in a different color make it possible to select the power tap settings of the hanging speaker. The cable is available in both black and white, making it as discrete as possible in any situation.





## Properties:



#### **Inner Conductors:**



#### **Product Features:**


Application AV & IT

Series Bulk & Accessories

# Physical Characteristics:

Inner conductor	Insulation	Material	PVC 1.8 mm (Ø)
		Colours	Black / White / Grey / Red / Green / Blue / Yellow / Orange / Purple / Brown
Outer jacket	Material		Flexible PVC 6.5 mm (Ø)
	Colours		Black
Type of cable			5-core loudspeaker cable
Inner conductor	Material		BC 23 x 0.15 mm (Ø) (OFC)
	Section		0.00062 "2
Filling			Cotton Yarn
Separator			Cotton paper
Inner conductor	American Wire Gauge		22 AWG
	Number of conductors		5
	Conductor twisting		Yes

### Cross sections:



# Variants:

- LSS504B/1 100 meter, black
- LSS504W/1 100 meter, white