



2 x Balanced signal / DMX-AES & 3G2.5 Power cable

Highlights:

- · Made in EU
- · All-in-one solution
- · Custom installation
- · Easy and fast installation
- · Combine multiple cables cores in one single cable

Product information:

The PAC252 is a hybrid power/audio cable which consists of 3 x 2,5mm² power section and two times a 2 x 0.22mm² 110 Ohm signal pair. The dual signal pair makes it ideal for applications where a stereo signal is needed or where the second pair is used as redundancy. The power and the 2 signal cables each have a separate jacket which makes it easy to split out the cables at the end.



Components:

- CableType: HMX224 24 AWG Balanced signal / DMX-AES cable
- CableType: HPC3G2.5 3G2.5 3 x 2.5 mm² PVC power cable

Certification:



Properties:





Product Features:

Application Rental & MI

Series Bulk & Accessories

Physical Characteristics:

Components		2 x HMX224
		1 x HPC3G2.5
Outer jacket	Material	Highflex PVC 18.0 mm (Ø)
	Colours	Black
Type of cable		Power & 2 x DMX-AES 110 Ω cable
Filling		Non-woven (PET/PA) tape


Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Flammability test	According EN 60332-1-2

Mechanical Characteristics:

Temperature range	Fixed installation	- 59 °F till + 158 °F
	Mobile installation	- 41 °F till + 167 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Cross sections:



Variants:

- PAC252/1 100 meter
- PAC252/3 300 meter

HMX224 24 AWG Balanced signal / DMX-AES cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



Physical Characteristics:

Inner conductor	Audio	Material		TC 7 x 0.2 mm (Ø) (OFC)
		Section		0.00034 "2
		American Wire Gauge		24 AWG
		Number of conductor	S	2
		Insulation	Material	PE 1.5 mm (Ø)
			Colours	Red / Blue
		Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap
			Drain wire	TC 7 x 0.2 mm (Ø) (OFC)
			Braiding	TC 7 x 16 x 0.1 mm (Ø) (OFC)
Filling				Non-woven (PET/PA) tape
Outer jacket	Material			PVC 5.0 mm (Ø)
	Colours			Black

Electrical Characteristics:

Max. conductor	DC resistance	85 (Ω / Km)
Max. shielding DC r	esistance	25 (Ω / Km)
Audio		47 (pF/m)
Characteristic impe	dance	110 Ω ± 10% Ω
Nom. Velocity of propagation		75 %
Return loss (dB)		(From 1 to 25 mHz) > 20 dB
Dielectric strength		(Cond/Shield) 1.2 (KV / 1 min. DC)
		(Cond/Cond) 0.5 (KV / 1 min. DC)

HPC3G2.5 3G2.5 3 x 2.5 mm² PVC power cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



Physical Characteristics:

Inner conductor	Power	Material		BC 48 x 0.25 mm (Ø) (OFC)
		Section		0.0039 "2
		American Wire Ga	uge	16 AWG
		Number of conductors		3
		Insulation	Material	PVC 3.7 mm (Ø)
			Colours	Blue / Brown / Yellow & Green
Outer jacket	Material			PVC 10 mm (Ø)
	Colours			Black

Electrical Characteristics:

Max. conductor	DC resistance	7.98 (Ω / Km)
Resistance	Insulation	> 200 M Ω / km
Rated voltage		Uo/U 300/500 V
Dielectric strength		2.5 (KV / 1 min. DC)