



# Highlights:

- Ultraflex™ Ultra flexible jacket
- 24 AWG thin and dense stranded conductors
- · 0.26 " (Ø) outer diameter
- · Oxygen free copper
- · 60 mm transparent shrink sleeve
- · Silver contacts, black metal XLR housing

### Product information:

The PRA736 is a high-quality microphone cable constructed using the ultra flexible PMC224 cable with break out and fitted with Neutrik NC3MXX-BAG and 2 times the Neutrik NC3FXX-BAG (Silver contacts, black metal XLR housing) connectors. The 24 AWG (0.22 mm²) thin & Dense stranded bare copper conductors are surrounded by a high coverage spiral shielding. In combination with the thick and soft PVC outer jacket, this provides a flexible but solid feel. The high-purity copper, high-coverage shielding and low capacitance guarantee an optimal signal transmission. The attached shrink sleeve allows custom labeling for easy identification. It comes in 1 length of 1.5 meter, providing solutions for all applications.

## Components:

- CableType: PMC224 Balanced microphone cable flex 2 x
  0.22 mm² 24 AWG UltraFlex™
- · Connector: NC3MXX 3 pole male cable connector
- · Connector: NC3FXX 3 pole female cable connector



#### Certification:



#### **Properties:**






### **Product Features:**

Application Rental & MI

Series Prime Series

# Wiring Diagrams:



### Variants:

• PRA736/1.5 - 1.5 meter