

Highlights:

- Duraflex™ extremely robust PUR jacket
- 24 AWG stranded conductors
- 0.32 " (Ø) outer diameter
- Oxygen free copper
- NE8MC compatible
- 50 micron gold plated connectors
- Double shielding (Al-foil + Braiding)
- Wired according to ANSI/TIA/EIA 568B (straight)
- 60 mm transparent shrink sleeve



Product information:

The PRD500 is a CAT5E UTP cable (PCT50SF) terminated with gold plated male RJ45 connectors at both ends. The PCT50SF networking cable specifically designed for the growing number of digital applications in the professional AV industry. Unlike any other CAT5E cable available on the market, the PCT50SF features Duraflex™ outer jacket constructed using a double-extrusion technique with a polyurethane outer and PVC inner jacket. The polyurethane outer jacket offers an excellent resistance against mechanical wear due to pulling, bending, cracking and UV exposure, while the PVC inner jacket keeps it easy to handle. The conductor section consists of 4 pairs with stranded 24 AWG conductors which guarantees an optimal signal transmission while the double shielding consisting of an overall aluminum foil surrounded by a braiding offers a high immunity to noise and interference caused by external devices. Supports 10Base-T, 100Base-TX and 1000Base-T gigabit networks.



Properties:

Shrink sleeve	Gold plated	CAT5E 100 MHz
PUR Polyurethane	Bi-jacketed	IEC 60332
HD Base T Compliant	Shielded	100Ω Impedance

Components:

- CableType: PCT50SF - Networking cable - CAT5E - SF/UTP - flex 0.22 mm² - 24 AWG - DuraFlex™

Product Features:

Application	Rental & MI
Series	Prime Series