

# PROMO6A-CLS215-CCA Sample pack CLS215-Cca

### Highlights:

- 16 AWG (1.5 mm²) thin and dense stranded conductors
- · Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass Cca-s1,d0,a1

#### Product information:

1 meter sample pack of the CLS215-Cca. The CLS215-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire. In addition to its Improved fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling.

The CLS2xx series consists of three models with individually polyolefin isolated conductors in sections ranging from 1.5 mm² (16 AWG) up to 4 mm² (11 AWG) which are composed of stranded bare copper wires. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.


More information about CPR compliant cables? Click here



#### Certification:



#### **Properties:**





#### Inner Conductors:



#### **Product Features:**

Application	AV & IT
	Rental & MI
Sprips	Rulk & Accessories

PROCAB - PROMO6A-CLS215-CCA - 03/11/2025 00:29 UTC

# Physical Characteristics:

Type of cable			2-core loudspeaker cable
EN50399 CPR Euroclass			Cca-s1b,d0,a1
Inner conductor	Material		BC 28 x 0.25 mm (Ø) (OFC)
	Section		0.0023 "2
	Number of conductors		2
	Insulation	Material	Polyolefin 2.5 mm (Ø)
Filling			None
Separator			None
Inner conductor	American Wire Gauge		16 AWG
	Insulation	Colours	Red / Blue
	Conductor twisting		Yes
Outer jacket	Material		Polyolefin 7 mm (Ø)
	Colours		Black

# Electrical Characteristics:

Max. conductor	DC resistance	13.3 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

# Cross sections:

