

# PROMO6A-CLS225-B2CA Sample pack CLS225-B2ca

### Highlights:

- 13 AWG (2.5 mm²) thin and dense stranded conductors
- · Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass B2ca-s1,d0,a1

#### Product information:

1 meter sample pack of the CLS225-B2ca. The CLS225-B2ca series are 2-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? Click here



#### Certification:



#### Properties:





#### Inner Conductors:



#### **Product Features:**

Application	AV & IT
	Rental & MI
Sprips	Rulk & Accessories

PROCAB - PROMO6A-CLS225-B2CA - 01/11/2025 00:07 UTC

# Physical Characteristics:

Type of cable			2-core loudspeaker cable
EN50399 CPR Euroclass			B2ca-s1b,d0,a1
Inner conductor	Material		BC 40 x 0.263 mm (Ø) (OFC)
	Section		0.0039 "2
	Number of conductors		2
	Insulation	Material	Polyolefin 3.5 mm (Ø)
Filling			None
Separator			None
Inner conductor	American Wire Gauge		13 AWG
	Insulation	Colours	Red / Blue
	Conductor twisting		Yes
Outer jacket	Material		Polyolefin 9.6 mm (Ø)
	Colours		Black

# Electrical Characteristics:

Max. conductor	DC resistance	7.98 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

# Cross sections:

