

Highlights:

- 13 AWG (2.5 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass Cca-s1,d0,a1

Product information:

1 meter sample pack of the CLS225-Cca. The CLS225-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Product Features:

Application	AV & IT
	Rental & MI
Series	Bulk & Accessories

Physical Characteristics:

Type of cable		2-core loudspeaker cable	
EN50399 CPR Euroclass		Cca-s1b,d0,a1	
Inner conductor	Material	BC 40 x 0.263 mm (Ø) (OFC)	
	Section	0.0039 "²	
Number of conductors		2	
Insulation	Material	Polyolefin 3.0 mm (Ø)	
Filling		None	
Separator		None	
Inner conductor	American Wire Gauge	13 AWG	
	Insulation	Colours	Red / Blue
Conductor twisting		Yes	
Outer jacket	Material	Polyolefin 8.5 mm (Ø)	
	Colours	Black	

Electrical Characteristics:

Max. conductor	DC resistance	7.98 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Cross sections:

