

Highlights:

- 11 AWG (4 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass B2ca-s1,d0,a1

Product information:

1 meter sample pack of the CLS240-B2ca. The CLS240-B2ca series are 2-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? [Click here](#)



- EN50399 CPR Euroclass B2ca-s1b,d0,a1

Certification:

B2CA
CPR

Properties:



Inner Conductors:



Product Features:

Application

AV & IT

Rental & MI

Series

Bulk & Accessories

Physical Characteristics:

Type of cable	2-core loudspeaker cable		
EN50399 CPR Euroclass	B2ca-s1b,d0,a1		
Inner conductor	Material	BC 48 x 0.31 mm (Ø) (OFC)	
	Section	0.0062 ^{“2}	
	Number of conductors	2	
	Insulation	Material	Polyolefin 4.5 mm (Ø)
Filling			None
Separator			None
Inner conductor	American Wire Gauge	11 AWG	
	Insulation	Colours	Red / Blue
	Conductor twisting		Yes
Outer jacket	Material	Polyolefin 11.7 mm (Ø)	
	Colours	Black	

Electrical Characteristics:

Dielectric strength	2 (KV / 1 min. DC)	
Rated voltage	500 V	
Max. conductor	DC resistance	4.95 (Ω / Km)

Cross sections:

