

### Product information:

The PRV158 is a HighFlex™ 75Ω coaxial video cable, which is specifically designed for HD-SDI and 3G-SDI digital video interconnections in the professional AV industry. The cable is solid but flexible constructed featuring a stranded high purity copper conductor (19 AWG), which is surrounded by a foamed polyethylene isolator. The shielding consists of a dual braiding which offers a high immunity against noise and interference caused by external devices, while offering a high flexibility and reliability for mobile applications. Both ends are terminated using HD BNC connectors allowing rigid and direct connections between compatible equipment. It can be used for a wide variety of mobile applications such as analogue video interconnections as well as HDTV digital SDI, HD-SDI and 3G-SDI.



### Components:

- CableType: PCX160 - 3G SDI coaxial video cable - RG6/U - flex 0.65 mm² - 19 AWG - HighFlex™
- Connector: NBNC75BRU11 - rearTWIST HD BNC cable connector

### Certification:



### Properties:



### Product Features:

Application	Rental & MI
Series	Prime Series

## Variants:

---

- PRV158/0.5 - 0.5 METER
- PRV158/1.5 - 1.5 METER
- PRV158/3 - 3 METER
- PRV158/5 - 5 METER
- PRV158/10 - 10 METER
- PRV158/20 - 20 METER