

# PRX160

## Cable reel - 3G-SDI - BNC female - BNC male - HighFlex™

### Highlights:

- 19 AWG stranded conductors
- Highflex™ solid & flexible jacket
- · Double braided shielding
- · 0.28 " (Ø) outer diameter
- · HD-SDI up to 85 meter
- · 3G-SDI up to 58 meter
- Oxygen free copper
- · 60 mm transparent shrink sleeve

#### Product information:

The PRX160 is a HighFlex<sup>™</sup>  $75\Omega$  coaxial video cable (PCX160) assembled on a lightweight, extremely strong and impact resistant reel (CDM310). The cable is solid but flexible constructed featuring a stranded high purity copper conductor (19 AWG), which is surrounded by a foamed polyethylene isolator. The shielding consists of a dual braiding which offers a high immunity against noise and interference caused by external devices, while offering a high flexibility and reliability for mobile applications. The cable end is terminated using a male BNC connector while chassis side is fitted with a female BNC connector. It can be used for a wide variety of mobile applications such as analogue video interconnections as well has HDTV digital SDI and HD-SDI.

#### Components:

- Reel: CDM310 Professional plastic cable reel Ø 312 mm
- CableType: PCX160 3G SDI coaxial video cable RG6/U flex 0.65 mm² - 19 AWG - HighFlex™
- Connector: NBNC75BRU11 rearTWIST HD BNC cable connector
- · Connector: NBB75DSG Neutrik Bulkhead BNC Solder



#### Certification:



#### Properties:











#### **Product Features:**

Application Rental & MI

Series Prime Series

#### Variants:

- PRX160/50 50 meter
- PRX160/100 100 meter

PROCAB - PRX160 - 02/11/2025 14:42 UTC