

Highlights:


- Parallel & separable wires
- 24 AWG stranded coaxial
- 3 x coaxial (RGB)
- Double shielding (Al-foil + Spiral)

Product information:

The RGB600 is a high quality RGB-video cable for all high resolution RGB-video interconnects. It contains 3 shielded coax cables, all with solid Oxygen free copper conductors, foamed polyethylene dielectric and braided shielding. The coax cables feature a high velocity of propagation and minimal return loss to ensure quality signal delivery on longer connections. Compatible with Neutrik BNC connector NBNC75BFH6.



Properties:



Inner Conductors:



Shielding:



Product Features:

Application	AV & IT
Series	Bulk & Accessories

Physical Characteristics:

Inner conductor	Insulation	Material	FPE 3.2 mm (Ø)
		Colours	Red / Green / Blue
Outer jacket	Material	Flexible PVC 3 x 6 mm (Ø)	
		Colours	Black
Type of cable	75 Ω coaxial video cable		
Inner conductor	Material	BC 20 x 0.12 mm (Ø) (OFC)	
		Section	0.00034 "²
		American Wire Gauge	24 AWG
		Number of conductors	3

Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 59 °F till + 140 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Cross sections:

