

Highlights:


- Parallel & separable wires
- 24 AWG stranded coaxial
- 3 x coaxial (RGB)
- Double shielding (Al-foil + Spiral)

Product information:

The RGB600 is a high quality RGB-video cable for all high resolution RGB-video interconnects. It contains 3 shielded coax cables, all with solid Oxygen free copper conductors, foamed polyethylene dielectric and braided shielding. The coax cables feature a high velocity of propagation and minimal return loss to ensure quality signal delivery on longer connections. Compatible with Neutrik BNC connector NBNC75BFH6.



Properties:



Inner Conductors:



Shielding:



Product Features:

| | |
|-------------|--------------------|
| Application | AV & IT |
| Series | Bulk & Accessories |

Physical Characteristics:

| | | | |
|-----------------|--------------------------|---------------------------|--------------------|
| Inner conductor | Insulation | Material | FPE 3.2 mm (Ø) |
| | | Colours | Red / Green / Blue |
| Outer jacket | Material | Flexible PVC 3 x 6 mm (Ø) | |
| | | Colours | Black |
| Type of cable | 75 Ω coaxial video cable | | |
| Inner conductor | Material | BC 20 x 0.12 mm (Ø) (OFC) | |
| | | Section | 0.00034 "² |
| | | American Wire Gauge | 24 AWG |
| | | Number of conductors | 3 |

Mechanical Characteristics:

| | | |
|-------------------|---------------------|------------------------|
| Temperature range | Fixed installation | - 104 °F till + 176 °F |
| | Mobile installation | - 59 °F till + 140 °F |
| Bending radius | Fixed installation | 6 x outer diameter |
| | Mobile installation | 8 x outer diameter |

Cross sections:

