

## Highlights:

---

- 13 AWG (2.5 mm<sup>2</sup>) thin and dense stranded conductors
- EN60332-1-2 CPR Euroclass Eca
- Parallel & separable wires
- Red stripe polarity identification
- Oxygen free copper conductors
- Meters indication marking

## Product information:

---

The RZ Series cables are parallel designed loudspeaker cables offering maximum flexibility and strength, ideal for a wide range of indoor applications. Each conductor is made of high-purity oxygen-free copper (OFC), ensuring excellent conductivity and long-term signal integrity. The conductors are fitted with a highly flexible PVC jacket. The two parallel conductors come in black, with one marked by a thin red line for easy polarity identification. These “all-round” loudspeaker cables are perfectly suited for various loudspeaker-level connections. Now featuring a CPR Euroclass Eca rating, the RZ Series ensures basic fire safety compliance, making them a reliable and cost-efficient choice for fixed installations. Always verify local regulations to confirm where Eca class cables are allowed. More information about CPR compliant cables? [Click here](#)




## Certification:

---



## Properties:

---



## Inner Conductors:

---



## Product Features:

---

Application	AV & IT
Series	Contractor Series

## Physical Characteristics:

---

Outer jacket	Material	Flexible PVC 4.0 x 8.0 mm (Ø)
	Colours	Black with red molded line
Inner conductor	Material	BC 210 x 0.12 mm (Ø) (OFC)
	Section	0.0039 <sup>“2</sup>
	American Wire Gauge	13 AWG
	Number of conductors	2

## Standards & regulations:

---

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Indoor / outdoor	Indoor
CPR Euroclass	Eca
Flammability test	According EN 60332-1-2


## Mechanical Characteristics:

---

Temperature range	Fixed installation	- 15 °C till + 80 °C
	Mobile installation	- 5 °C till + 15 °C

## Cross sections:

---



## Electrical Characteristics:

---

Max. conductor	DC resistance	0.7 Ω / 100 m
Dielectric strength		1200 V/min
Rated voltage		300 V

## Variants:

---

- RZ25-ECA/1 - 100 meter