

Highlights:

- 11 AWG thin and dense stranded conductors
- Parallel & separable wires
- Color coded polarity identification

Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.



Properties:



Inner Conductors:



Product Features:

Application	AV & IT
Series	Bulk & Accessories

Physical Characteristics:

Type of cable		2-core loudspeaker cable
Inner conductor	Material	BC 50 x 7 x 0.12 mm (Ø) (OFC)
	Section	0.0062 "²
	Number of conductors	2
Outer jacket	American Wire Gauge	11 AWG
	Material	Flexible PVC 5 x 10 mm (Ø)
	Colours	Black with red molded line


Mechanical Characteristics:

Temperature range	Fixed installation	- 104 °F till + 176 °F
	Mobile installation	- 77 °F till + 158 °F
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Capacitance	Cond/Cond	128 pF / m @ 1 kHz
Lead resistance		0.5 Ω / 100 m
Cable Crosstalk		Min. 74 dB / 100 m

Cross sections:



Variants:

- RZ40/1 - 100 meter