

Highlights:

- 11 AWG thin and dense stranded conductors
- Parallel & separable wires
- Color coded polarity identification

Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.



Properties:



Inner Conductors:



Product Features:

| | |
|-------------|--------------------|
| Application | AV & IT |
| Series | Bulk & Accessories |

Physical Characteristics:

| | | |
|-----------------|----------------------|-------------------------------|
| Type of cable | | 2-core loudspeaker cable |
| Inner conductor | Material | BC 50 x 7 x 0.12 mm (Ø) (OFC) |
| | Section | 0.0062 "² |
| | Number of conductors | 2 |
| Outer jacket | American Wire Gauge | 11 AWG |
| | Material | Flexible PVC 5 x 10 mm (Ø) |
| | Colours | Black with red molded line |


Mechanical Characteristics:

| | | |
|-------------------|---------------------|------------------------|
| Temperature range | Fixed installation | - 104 °F till + 176 °F |
| | Mobile installation | - 77 °F till + 158 °F |
| Bending radius | Fixed installation | 8 x outer diameter |
| | Mobile installation | 10 x outer diameter |

Electrical Characteristics:

| | | |
|-----------------|-----------|--------------------|
| Capacitance | Cond/Cond | 128 pF / m @ 1 kHz |
| Lead resistance | | 0.5 Ω / 100 m |
| Cable Crosstalk | | Min. 74 dB / 100 m |

Cross sections:



Variants:

- RZ40/1 - 100 meter